## Perform Series, Leg Extension

The Perform Series Leg Extension isolates the quadriceps through a single joint, knee extension movement. The adjustable back and ankle pad ensure sound biomechanics, increases comfort and encourages full quadriceps contraction without hamstring flexibility limitations.





Water Bottle Holder

Instuctions placard





High-density Poly-foam

Adjustable Ankle Pad



## **Technical Specifications**

| Rating                 | Commercial   |  |
|------------------------|--|--|
| Upholstery             | High-density poly-foam and double stitches offer comfort and endurability  |  |
| Adjustments            | Adjustable back and ankle pads to allow easy operation and comfort   |  |
| Tubing                 | Tube of the functional part is primarily at a 3mm thickness. The weight stack cage is with D-shape tube size: 95 x 81.1 x 3mm and a racetrack tube size: 50 x 100 x 3mm which ensure ultra-durability and stability. |  |
| Instructions<br>Plaque | Instructions placards to review proper set-up, movement and muscles trained  |  |
| Shroud                 | Translucent ABS shroud at a thickness of 3.2mm ensures ultra-durability and shock resistance.  |  |
| Weight Stack           | 91kg<br>200lbs   |  |
| Product Weight         | 133.lkg<br>293lbs  |  |
| Maximum User<br>Weight | 150kg<br>330lbs  |  |
| Dimensions             | L 157.5 x W 118.9 x H 150.6 cm<br>L 62 x W 46.8 x H 59.2 inches  |  |

## **Key Features**

| Space efficient design requires minimal floor space   | • |
|---|---|
| Self-lubricate American loos™ cable with nylon-coated 12 complex fiber ensures service life more than 250 thousand times. | • |
| Water bottle holder fixed on the cage is within reach.  | • |
| Ergonomic handlebars in TPV material with<br>aluminium ring limit offers comfort and<br>security during a workout         | • |
| All dynamic components are shielded for safety purpose  | • |
| Lathed pulley with bearings of less tolerance ensure smooth movement  | • |
| Meets EN957 safety regulation   |   |



